

STATE OF WASHINGTON
DEPARTMENT OF CONSERVATION
AND DEVELOPMENT

WELL LOG

No. A. 6569

Date 1-2, 1963

Record by well driller

Source driller's record

Location: State of WASHINGTON

County Island

Area

Map

1/4 sec. 22 T 32 N, R. 2 E

Drilling Co. A. G. Kounkel

Address Box 216-A, Stanwood, Wash.

Method of Drilling cable Date 9-24, 1949

Owner C.W. Brokaw

Address Stanwood, Wash.


Land surface, datum ft. above
below

Diagram of Section

File number

3212E-22H

CORRE- LATION	MATERIAL	THICKNESS (feet)	DEPTH (feet)
------------------	----------	---------------------	-----------------

(Transcribe driller's terminology literally but paraphrase as necessary, in parentheses. If material water-bearing, so state and record static level if reported. Give depths in feet below land-surface datum unless otherwise indicated. Correlate with stratigraphic column, if feasible. Following log of materials, list all casings, perforations, screens, etc.)

	Blue clay	0	17
	" " with gravel		
	(little water) streaks	15	32
	Clay and silt	103	135
	Silty sand (little water)	14	149
	Blue clay	21	170
	Coarse sand & gravel-water	8	178
	Artesian pressure 13# per sq.inch		
	Water controlled by cap.		
	Yield: 20 g.p.m. 20' DD at 4 hrs.		
	Artesian flow 4 g.p.m. (9-24-49)		
	CASING:		
	8" diam. from 0 to 172 ft.		
	Screen: Armco (Johnson) 8"x6"x#30 slot		
	Surface was sealed to a depth of 10'.		
	with clay.		



WASHINGTON STATE
DEPARTMENT OF
ECOLOGY

Well Tagging Form

Unique Well Tag No: APH261

RECORD VERIFICATION (check ☒ one)

- ☒ Well Report available *(please attach this form to the well report and submit it to the Ecology Regional Office near you)*
- ☐ Verification inconclusive
- ☐ Well Report not available

WELL OWNERSHIP IF DIFFERENT FROM WELL REPORT

Name: Rocky Point Water Association

Street Address: 1059 SCENIC AVE. N.

City: CAMANO ISLAN

State: WA

RECEIVED

APR 24 2007

DEPT. OF ECOLOGY

WELL LOCATION IF DIFFERENT FROM WELL REPORT

Well Address: Brokaw Rd/R23222-270-5250

City: Camano Island

County: Island

T. 32N R. 02E W.M. Sec. 23 SW 1/4 of the NW 1/4

FOR AGENCY USE ONLY

Latitude: 48 14.87601

Longitude: 122 31.58209

Elevation at land surface 56 feet meters (circle one)

Additional Information, if available:

☐ Location marked on topographic map *(please attach)*

☐ Location marked on air photo *(please attach)*

- ☒ GPS
- ☐ Topographic Map
- ☐ Survey
- ☐ Computer generated

- ☐ Digital Altimeter
- ☐ Topographic Map
- ☒ Other: Computer Generated from
DEM and GPS XY Coordinates

Tag placed and well
GPS'd by:



FOR AGENCY USE ONLY

WELL CHARACTERISTICS

Physical Description of well (size of casing, type of well, housing, etc.)

Pumphouse And Wellhead Are On The Corner of Brokaw And Rocky Point Dr--Next To Totem Pole And Silver Gate.

Location of Well Identification Tag:

Was supplemental tag needed for easy of identifying well?

☐

Yes

☒

No

If yes, where was tag placed?

D	C	B	A
E	F	G	H
M	L	K	J
N	P	Q	R

SECTION: 32N/02E-23

COMMENTS:

FOR ECOLOGY WATER RESOURCES PROGRAM ONLY

Water Right #

Date Issued:

Circle One:

Application

Permit

Certificate

Claim

Exempt

STATE OF WASHINGTON.
DEPARTMENT OF CONSERVATION
AND DEVELOPMENT

WELL LOG

No. A. 6569

Date 1-2, 1963

Record by well driller

Source driller's record

Location: State of WASHINGTON

County Island

Area

Map

1/4 sec. 22 T 32 N, R. 2 E

Diagram of Section

Drilling Co. A. G. Kounkel

Address Box 216-A, Stanwood, Wash.

Method of Drilling cable Date 9-24, 1949

Owner C.W. Brokaw

Address Stanwood, Wash.

Land surface, datum ft above
below

CORRE- LATION	MATERIAL	THICKNESS (feet)	DEPTH (feet)
------------------	----------	---------------------	-----------------

(Transcribe driller's terminology literally but paraphrase as necessary, in parentheses. If material water-bearing, so state and record static level if reported. Give depths in feet below land-surface datum unless otherwise indicated. Correlate with stratigraphic column, if feasible. Following log of materials, list all casings, perforations, screens, etc.)

	Blue clay	0	17
	" " with gravel		
	(little water) streaks	15	32
	Clay and silt	103	135
	Silty sand (little water)	14	149
	Blue clay	21	170
	Coarse sand & gravel-water	8	178
	Artesian pressure 13# per sq.inch		
	Water controlled by cap.		
	Yield: 20 g.p.m. 20' DD at 4 hrs.		
	Artesian flow 4 g.p.m. (9-24-49)		
	CASING:		
	8" diam. from 0 to 172 ft.		
	Screen: Armco (Johnson) 8"x6"x#30 slot		
	Surface was sealed to a depth of 10'.		
	with clay.		

Turn up

Sheet . of .

32,126-22H
file number

RECEIVED

APR 24 2007

DEPT. OF ECOLOGY